





## SecurView Wireless Internet Camera TV-IP212W (A1.OR)

The Wireless 2-Way Audio Internet Camera transmits real-time high quality video and audio over the Internet. See, hear and talk to people, in your camera's from any Internet connection. Complimentary SecurView camera management software allows you to monitor what you value most at home or at work.

The camera provides crystal clear MPEG4 video streams over a secure encrypted internet connection. A built-in microphone and optional speakers accommodate 2-way audio communication. Advanced intuitive software includes motion detection recording, email alerts, scheduled recordings and progressive search options. This cameras brilliant image quality, USB flash support and 2-way audio make it ideal for home, small office and business use.

- FEATURES Compatible with wireless g and b devices.
  - Advanced encryption modes include WEP, WPA-PSK and WPA2-PSK
  - Built-in USB port allows you to store still image directly onto a USB flash or hard drive\*
  - Supports TCP/IP networking, SMTP Email, HTTP, Samba and other Internet protocols
  - High quality MPEG-4 and MJPEG video recording with up to 30 frames per second
  - Supports 3GPP live video viewing via 3G mobile phone \*\*
  - · Hear and talk to people in your camera's viewing area through your computer
  - · Record streaming video to your computer and Network Storage
  - · Supports still image snapshot to FTP, Email and Flash drive
  - · Motion detection with Email notification
  - Supports two adjustable motion detection windows with just-in-time snapshot
  - · Supports time stamp overlay
  - Quick Universal Plug and Play installation
  - Free SecurView<sup>™</sup> software: view and record up to 16 cameras simultaneously \*\*\*
  - 3-year limited warranty
  - USB port supports up to 500mA power device with FAT16/32 format
  - \*\* The 3G service from a mobile phone provider is required
  - \*\*\* Monitoring multiple cameras may require a high performance CPU

# SecurView Wireless Internet Camera TV-IP212W (A1.OR)

### **SPECIFICATIONS**

mage Sensor	1/2 O-l-s OMOO O-s		
Sensor	• ¼" Color CMOS Sensor		
Resolution	• 640 x 480 pixel		
Fixed Lens	• f: 4.6mm, F: 2.8 (Board Lens)		
Viewing Angle	• 60 Degree		
Minimum Illumination	• 0.5Lux @ F2.0		
Audio			
Microphone Input	• Internal Omni-Directional • Sensitivity: -48dB + 3dB • Response Frequency: 50 ~ 16000Hz		
Audio Output	3.5mm Speaker Output Jack		
Format	PCM/AMR (Mono)		
/ideo/Image Setting			
Video Format	MPEG4(Simple Profile), MJPEG, 3GPP		
Image Frame Rate	• 30fps @VGA, QVGA, QQVGA		
Frame Rate Setting	• 1 ~ 30fps		
Compression Ration Setting	• 5 Levels		
Resolution	• 640 x 480, 320 x 240, 160 x 120		
Exposure Control, White Balance, Gain Control	Automatic		
Image Setting	Adjustable brightness, contrast, saturation		
Flip Images	Vertical / Horizontal		
Light Frequency	• 50Hz, 60Hz or Outdoor		
Communication			
LAN	• 10/100Mbps Auto MDIX		
Protocol	• HTTP, FTP, TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, PPPoE, UPnP, RTP, RTSP, RTCP		
System			
CPU	ARM9 base		
RAM	32Mbyte SDRM		
ROM	8Mbyte Nor Flash		
OS	• Linux		
Bystem Requirement			
CPU	Pentium III 350MHz or above		
Memory Size	• 128MB or above		
Resolution	800 x 600 or above		
Browser	Internet Explorer 6.0 or above		
Supported OS	Windows 2000/XP/Vista		
	(SecurView <sup>TM</sup> Software)		
CPU CPU	Pentium 4 1GHz or above		
	• 512MB or above		
Memory Size			
Resolution	1024 X 768 or above Windows 2000/XP/Vista		




# SecurView Wireless Internet Camera TV-IP212W (A1.OR)

#### **SPECIFICATIONS**

Physical/Environmenta			
Dimension	• 70 x 100 x 57mm (2.67 x 3.94 x 2.95 in.)		
Weight	Camera: 170g (6 oz.); Stand: 135g (4.76oz.)		
Power	5V DC, 2.5A External Adapter		
Power Consumption	8 Watts (Max)		
LEDs	Power (Orange), Link (Green)		
LED	Enable/Disable Support		
Temperature	• Operating: 0°C ~ 45°C (32°F ~ 113°F); Storage : -10°C ~ 60°C (14°F ~ 140°F)		
Wireless			
Standard	• IEEE 802.11b/g		
Security	64/128-bit WEP, WPA-PSK, WPA2-PSK		
Antenna	2dBi Detachable Reverse SMA Connector		
Other			
USB Port	• USB 1.1 (Type 1)		
USB POR	Up to 500mA Power Device with FAT16/32 Format		

#### **NETWORKING SOLUTIONS**



#### PACKAGE CONTENTS

•	ΤV	-IF	21	2W
	ı v	- 11	_	∠ v v

- Utility CD-ROM
- Multi-Language Quick Installation Guide
- Camera stand
- 1.8m Cat. 5 Fast Ethernet Cable
- Power Adapter (5V DC 2.5A)

#### RELATED PRODUCTS

TV-IP212	SecurView Internet Camera
TV-IP312	SecurView Day/Night Internet Camera
TV-IP312W	SecurView Wireless Day/Night Internet Camera

#### ORDERING INFORMATION

### TRENDNET

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: <u>www.trendnet.com</u> Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061